

Dynamic Mix 3.0

Up to € 15,000.- savings
of operating expenses **per**
year possible*

DYNAMIC MIXER WITH
DISPOSABLE MIXING CHAMBER
AND **TWO COMPONENT SWIVEL**
JOINT FOR INTEGRATION INTO
MANUAL SEALING PLANTS



BENEFITS

- Freezer or solvent flushing pump no longer required
- No more loss of material through purging processes
- Saving of costs for disposal of waste material**
- No more necessity for cleaning of Z-swivel joint
- No purchase of trumpet mixer required
- Less attrition of the plant by lowering the pressure level to approximately 120 bar

Dimensions	Length	Width	Height
	700 mm	150 mm	200 mm
Admissible operating pressure	450 to 1,000 cm ³ /min		
Maximum dyn. operating pressure	200 bar		
Max. air pressure	6 bar		
Weight	4,350 g		

PERFECT MATCH WITH **ECOSTAR EVO**

Optionally available as integrated in Ecostar evo-series or as retro-fit kit for existing installations.

*Depends on material and production parameters



YOUR GLOBAL PARTNER IN **METERING AND MIXING TECHNOLOGY**

- Processing and application of single and multi component adhesive and sealants
- Ambient or temperature conditioned equipment
- Complete systems for manual or fully automatic processes
- Innovative process control and verification